



# FLEXO EXPOSURE & WATER WASH PROCESSING EQUIPMENT

## POINT LIGHT EXPOSURE SYSTEMS

### OV 20-FLEX



**OV 20-FLEX**  
**Exposure Area 18"x24" (45x60cm)**  
 208-240 volts / 16 amps  
 3000, 2000, 1200 watts  
 36"x40"x30" (91x102x76cm)

### OV 33-FLEX



**OV 33-FLEX**  
**Exposure Area 24"x30" (61x76cm)**  
**Options:**  
 Mylar frames vs. glass  
 Motorized UV filter  
 Crating  
 208-240 volts / 40 amps (380v option)  
 8000, 4000, 2000 watts  
 89"x48"x72" (226x122x183cm)

### OV 45-FLEX



**OV 45-FLEX**  
**Exposure Area 30"x40" (76x102cm)**  
*\* Includes belt reflector*  
**Options:**  
 Mylar frames vs. glass  
 Motorized UV filter  
 Drawers & base cabinet  
 Crating  
 208-240 volts / 50 amps (380v option)  
 8000, 4000, 2000 watts  
 95"x58"x79" (241x147x201cm)

### OV 60-FLEX



**OV 60-FLEX**  
**OV 60D-FLEX double sided**  
**Exposure Area 40"x60" (102x152cm)**  
**Options:**  
 Mylar frames vs. glass  
 Motorized UV filter  
 Crating (2 crates)  
 208-240 volts / 90 amps (380v option)  
 16000, 8000, 4000 watts  
 127"x85"x89" (323x216x226cm)

### OV 40-Chilled Bed



**OV 40-FLEX**  
**Exposure Area 30"x40" (76x102cm)**  
**Options:**  
 Motorized UV filter  
 Drawers & base cabinet  
 Crating  
 208-240 volts / 50 amps (380v option)  
 8000, 4000, 2000 watts  
 51"x68"x80" (130x173x183cm)

## WATER WASH PROCESSORS & RADIOMETER

### W30



**Water Wash Combination Processor**  
**Max plate size 24"x30" (61 x 76cm)**  
 Plate thickness from 1.0 mm – 2.84 mm  
 Auto-reversing permanent adhesive plateholder  
 Exposure drawer with flood lamps  
 Two dryer drawers with pulsed hot air  
 De-tack / post exposure drawer  
 220/240V 50/60HZ / 25 amp  
 40"x42"x48" (102x10 x122cm)  
 720 lbs / 327 Kg

### W92



**In-line Water Wash Processor**  
**W92-FL with drying, post expose & UVC**  
**Max plate size 36"x48" (92 x 120cm)**  
 Max. Plate Size: 900mm x 1200mm  
 Plate thickness from 1.0 mm – 2.84 mm  
 Automatic in-line processing  
 Pulsed hot air drying  
 De-tack / post exposure drawer  
 230/400V / 50/60Hz / 3 Ph + net + gnd / 30 amp  
 98"x59"x44" (250x150x112cm)  
 1000 lbs / 454 Kg


### Filters



#### Recurculating Water Filter

FIRST FILTER	Each
200-3C428	Case of 6
SECOND FILTER	Each
200-3A428	Case of 6
SEPARATION FILTER	
301-55294	Each
System uses two	Case of 2

### Spectramatch Lamps Metal Halide Lamps



Spectral Output	Photopolymer	
Model	L1261	L1281
Wattage	1000-5000	2000-8000
Light Source	AL23-53	AL83-96

### UV Radiometer



#### Accumeter

- 2 channels & 3 spectral ranges
- Records mWatts & milliJoules
- Peak intensities & relative intensity
- SPC Software, downloads to PC
- Sensors work under vacuum

#### Options:

- Meter, UV probe & case only
- UV Dual Sensor Probe
- UVC Germicidal Probe
- Software and cable